

Fixed Gas Comparison Chart

BRAND	ANALOX		MSA		CROWCON		TELEDYNE		HONEYWELL	
MONITOR	A50	AX60+	S5000	Ultima X5000	Xgard Bright	Smart 3G-D2	OLCT 100	CTX300	Sensepoint XCD	XXN
DIMENSIONS	6.9"/175mm x 4"/106mm x 2.6"/67mm (w x h x d)	w 3" / 72mm h 5.1" / 132mm d 2" / 52mm	6.37" x 5.38" x 4.25" (162 x 137 x 108 mm)	5.88" x 5.71" (150 x 145 mm)	Aluminium enclosure: 156 x 166 x 109mm (6.1 x 6.5 x 4.3inch)	H145 x W187 x D108 mm (5.7 x 7.4 x 4.25ins)	135 x 133 x 84 5.43 x 5.24 x 3.31	H 136mm x W 130mm x D 69mm	H 22.5 cm W 16.4 cm D 9.9 cm	H 22.5 cm W 16.4 cm D 9.9 cm
IP RATING	IP65	IP55	IP66	IP66	IP65	IP65	IP66	IP54	IP66	IP66
GAS OPTIONS	CO2 Specifically	CO2, O2, CO Options	73+ gases	80+ gases	21+ gases	44+ gases	25+ gases	22+ gases	18+ gases	21+ gases
RESPONSE TIME	60 Seconds	<30 seconds (CO2)	Gas Dependent	Gas Dependent	Gas Dependent	Sensor Dependent	Gas Dependent	Gas Dependent	Gas Dependent	Gas Dependent
WARRANTY	5 years	5 years on electronics	Transmitter 2 years	Transmitter 2 years	2 year	2 years	3 years	2 years	1 year	1 year

